

B- SERIES 6" BOOSTER PUMP



Add this product for Compare

Technical Specification

Booster Pump is a Centrifugal Pump, It can Discharge the liquid to extended distance. It can be attached with electric motor or Engine. It just need Primed liquid and with dual Mechanical Seal & Oil Tub.

The max Head:	42 Mtr
Max Flow:	90L/s
Max Solid:	25 mm
Suction Lift:	Suction and Discharge 6" Table D Flange
L x W x H:	675x540x500
Original:	Any type of Quick coupling M,B,E & I Types
Weight:	190 Kg. with Frame for Motor

B-SERIES 6"



Add this product for Compare

Technical Specification

Its Centrifugal Self priming Pump with vacuum system. (Fabricated Priming tank and Discharge Head, Mild Steel Volute Cast Iron) and with dual Mechanical Seal & Oil Tub. It Prime automatically from dry for De-watering in Construction and Civil engineering.

The max Head:	42 Mtr
Max Flow:	90L/s
Max Solid:	25 mm
Suction Lift:	9 mtr
L x W x H:	2130x1300x1700
Original:	1. Any type of Quick Coupling M,B,E & L type, 2. Stainless Steel Casted Volute and Stainless Steel Fab
Weight:	730 Kg. (with Pump and 4 Wheel Trailer) , 1115 Kg. (with Kirloskar HA394 Engine)