

## Control Valve


Our array of **control valves, motorized control valves, single seated control valves and double seated control valves** are widely appreciated for their performance and durability. Manufactured with the aid of latest technology, the **control valves are used for controlling the flow of gasses and liquids**. Our control valves can be supplied with the following specifications :

Type	Control Valve Single Seated / Double Seated / 2 Way / 3 Way
Size	From 25 mm to 250 mm
Pressure Rating	Class 150, 300, 600
Design Pressure	Up to 200 PSIG
Design temperature	Up to 100 Deg. C
Body Material	C. I., C. S., SS 304, SS 316, Alloy 20, Monnel
Trim Materials	AISI 410 / 304 / 316
End Connection	Flanged End

### Diaphragm Operated Butterfly Valve

Our diaphragm operated **Butterfly valves are solution to the requirements of a large number of industries**. Robustly constructed, our Diaphragm operated Butterfly valves are available at the most competitive prices.


#### Technical Specifications:



Type	Diaphragm Operated Butterfly Valve
Size	From 2" to 36"
Design Pressure	Up to 600 lbs
Design temperature	Up to 650 Deg. C
Body Material	C. I., C. S., SS 304, SS 316, Alloy 20, Monnel
Trim Materials	AISI 410 / 304 / 316
End Connection	Wafer Type Design
Actuator Type	Spring Diaphragm Cylinder

### Single Seated / Double Seated

Our range of control valves also includes **single seated/double seated valves, which are precision engineered and reckoned for their durability**. These are available in following technical specifications:



Type	Single / Double Seated Control Valve
Size	From 1/2" to 8" for single seated & 1" to 12" for Double Seated
Pressure Rating	Class 150, 300, 600
Design Pressure	Up to 900 PSIG
Design temperature	Up to 100 Deg. C to 850 Deg. C
Body Material	C. S., SS 304, SS 316, Alloy 20, Monnel
Trim Materials	AISI 410 / 304 / 316
End Connection	Screwed upto 2" Socket Weld End up to 3" Flanged confirming to ANSI, DIN,IS,BS
Actuator Type	Spring Diaphragm Cylinder
Characteristics	Quick-Opening, Equal Percentage & Linear
Bellows Seal	Stainless Steel & PTFE
Packing	Teflon, Teflon Abbestos Graffited asbestos

## Motorized Control Valve

We hold expertise in **manufacturing motorized control valve**, which have a electrical actuator directly mounted on control valve **for controlling the flow of material**. Available in various sizes, our range can be customized as per customer's requirements.



Type	Globe / Gate / Ball / Butterfly Motorized Control Valve
Size range	from 15mm to 300mm
Body Material	C. S., SS 304, SS 316, Alloy 20, Monnel
Trim Materials	AISI 410 / 304 / 316
End Connection	Screwed upto 2" Socket Weld End up to 3" & Flanged confirming to ANSI, DIN,IS,BS
Actuator Type	Electrical, Reversible
Power Supply	24 / 110 / 230 VAC Single Phase, 50 Hz
Input Single	Changeover contacts / 4-20 mA DC / 0-10 VDC, Up-down relay from PI, PID
Enclosure	Weather-proof (IP-55), (IP 67)