

Tilting Positioner

The tilting positioner can be used for kinds of pipe to pipe to flange, shafts, disks and cylinders. with compact design, good appearance and easy to operate. It's the ideal welding auxiliary for oil and gas, metallurgy, electricity power, chemicla equipment, metal profile and soon.



Main specification

Specification	MTP500	MTP1000	MTP3000	MTP5000	MTP10000
Max.payload(Kg)	500	1000	3000	5000	10000
Tilting speed (rpm)	0.6	1	0.2		
Rotating speed (rpm)	0.13-1.3	0.12-1.2	0.05-0.5		
Rotating speed Adjustment	AC Variable Speed				
Tilting angle(°)	Motorized0-135			Motorized0-130	
Plate Diameter(mm)	Φ800	Φ900	Φ1300	Φ1600	Φ1800
Max.eccentricity(mm)	150	150	200	200	200
Max. distance of gravity center (mm)	200	200	300	300	400
Rotating Motor Power (Kw)	0.37	0.75	1.5	2.2	3

Tilting Motor Power (kw)	0.37	0.75	1.5	2.2	4
Product Code	330401- 0000- 0000-00	330402- 0000- 0000-00	330403- 0000- 0000-00	330404- 0000- 0000-00	330405- 0000-0000- 00