

Fasteners

Hex Screw

Manufacturer and supplier of HEX SCREWS. These Hex Screws made from stainless steel are available in various specifications, size and length as per clients requirements. Wide range is available For HIGH/ LOW Temperature and Pressure as well as other working Temperature.



Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable

MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 200 MM INCHES - 3/8" TO 8"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

Hex Bolt

Manufacturer and supplier of HEX BOLTS. These Hex Bolts made from stainless steel are available in various specifications, size and length as per clients requirements. Wide range is available For HIGH/ LOW Temperature and Pressure as well as other working Temperature.



Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable

MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12,9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 200 MM INCHES - 3/8" TO 8"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

U Bolt

Manufacturer and supplier of U Bolt. These U Bolt made from stainless steel are available in various specifications, size and length as per clients requirements. Wide range is available For HIGH/ LOW Temperature and Pressure as well as other working Temperature.

Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable



MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 1000 MM INCHES - 3/8" TO 40"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

Plain Washer

Plain Washers, which are widely known for their high strength, hardness and corrosion resistance. These are manufactured using quality raw material. Plain Washers are widely demanded in various automobile, construction, electrical and engineering industries.

Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable



MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 1000 MM INCHES - 3/8" TO 40"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

Carriage Bolt

Manufacturer and supplier of Carriage Bolt. These Carriage Bolt made from stainless steel are available in various specifications, size and length as per clients requirements. Wide range is available For HIGH/ LOW Temperature and Pressure as well as other working Temperature.



Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable

MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 1000 MM INCHES - 3/8" TO 40"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

Flange Bolt

Manufacturer and supplier of Flange Bolt. These Flange Bolt made from stainless steel are available in various specifications, size and length as per clients requirements. Wide range is available For HIGH/ LOW Temperature and Pressure as well as other working Temperature.



Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable

MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 200 MM INCHES - 3/8" TO 8"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

Spring Washer

Spring Washers, which are widely known for their high strength, hardness and corrosion resistance. These are manufactured using quality raw material. Spring Washers are widely demanded in various automobile, construction, electrical and engineering industries.

Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable



MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 1000 MM INCHES - 3/8" TO 40"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE

Threaded Rod

Extensive range of **Threaded Rods** is available with us. Conforming to the defined parameters of the industry, these offered rods are being demanded for their longer service life, sturdiness, dimensional accuracy and resistance against corrosion. Threaded rods available in various sizes and specifications so as to meet divergent demands of the clients. Along with this, our clients can avail the best customized range made as per their detailed specifications from us.



Features

- International Standards
- High Quality Precision
- High Corrosion Resistance
- Durable

MATERIAL	STAINLESS STEEL : ASTM 202, 304/304L, 316/316L, 316 S33, DUPLEX 2205/S31803 HIGH TENSILE ASTM A 193 (GR B7, B7M, B6, B16), ASTM A 320 (GR L7) IS GRADES 8.8, 10.9, 12.9 ETC
GRADES	ISO DIN 4.6; 6.6; 8.8; 10.9; 12.9; AND TO B.S & AISI ISO DIN P4; P6; P8; P10 AND TO B.S & AISI. ASTM A 193/ B7/ B6/ B8/ B8M/ B8T/ B16 ASTM A 320/ L7/ L43/ B8L/ B8M A 194/ 2H/ 4/ 6/ 7/ 8/ 8L/ 8M/ 8T
STANDARD	METRIC - DIN 933 , DIN 931 , ISO 4014 , ISO 4017 , IS 1363 / 4 INCHES - BS 1083 , ANSI B18.2.1
SIZE IN DIA	METRIC - M4 - M48 INCHES - 3/16" - 4"
SIZE IN LENGTH	METRIC - M6 TO 1000 MM INCHES - 3/8" TO 40"
MANUFACTURING PROCESS	COLD FORGE / HOT FORGE