

Super Mill

High Capacity Multi Mill



▼ Beaters Assembly



CHITRA Super Mill / High Capacity Multi Mill is a self contained portable unit useful for high speed GRANULATING, PULVERISING, MIXING, SHREDDING AND CHOPPING, etc., of a wide range of wet and dry materials without special attachments.

As compared to the four common principles of size reduction i.e. grinding, compression, impact and shearing, which often do not produce controlled size reduction, this machine utilizes the principle of variable force swing hammer blades having both knife and impact edges rotating with a carefully selected screen to control size reduction.

Flow path of material in vertical rotor machine is streamlined. During communication, material entering the chamber travels to the periphery and passes through the screen tangentially and radially, avoiding chocking and temperature rise.

Operation

SUPER MILL / HIGH CAPACITY MULTI MILL is designed to utilize the principle of variable force swing beaters having both knife and impact edges rotating within a selected screen to control the particle reduction. Material fed in to the processing chamber moves to the periphery and passes through the screen radially and tangentially. Finally the processed material gets collected in to the container kept below the processing chamber.



Special Designed ▶
Charging / Discharging Hopper



Super Mill

High Capacity Multi Mill



Special Features

- Suitable for dry and wet granules.
- All contact parts are made out of SS316 quality material. (SS316 L quality is optional)
- Castor wheel provided for the ease of mobility.
- Sieves available in sizes of 0.5 to 12mm hole dia.
- 14 nos. beaters with knife edges & impact edges & 02 nos. scrapper blades.
- In cGMP Model complete body covered with SS304 and polished to the matt finish & in Standard Model excluding product contact parts, all other parts made out of C.I. or M.S. and coloured.
- Machine rated for continuous operation.
- Higher output with process uniformity.
- All contact parts can easily be dismantled and cleaned for change of product.
- Wide range of SS perforated screens available
- Machine portable on castor wheels.
- Reversible direction of blade rotation.
- Different size of screen / speed / number of blade / direction of rotation of blade can be selected.
- **Out Put upto 300 to 350 Kgs.** (Depending upon the products, sieves size, speed and the reduction required in size of products.)

Optional - (will be provided on extra cost on your demand)

- Contact parts made out of SS316 L instead of SS316.
- Providing flame proof drive motor along with flame proof starter and flame proof reversible switch.
- Variable frequency drive for the variable speed of operator.
- Vacuum loading system fore charging the material.
- Stand for IPC. (Intermediate product container) Recommended
- Extra sieves available in sizes of 0.5 to 12 mm hole dia. made out of SS304 / SS316 / SS316 L.

Application

Pharmaceuticals, Chemicals, Cosmetics, Ceramics, Colours, Dyestuff, Food Products, Pesticides, Fertilizers, Spices, Detergents, Insecticides, Plastics and Resins Industries.

