

Corrugation Machine

The oblique high speed model offers a high rate of production and enhanced efficiency. The flute rollers mounted on the roller bearings, for smoother running and longer life, impart the proper impression on the board. Dancing rolls are provided to eliminate the effect of improper winding of paper on the finished product. The machine is provided with motorized self loading twin shaft reel stand with 3 unwinding shafts. Shaftless hydraulic reel stand is recommended for this machine. The machine is to be heated by steam, Two preheating cylinders are provided with the machine.



Size	Motor H.P.	Heating Load K.W.	Weight Apprx.{MT}	Floor Space
42"	7	19	4	7.5'x15'
52"	7	22	4.5	8'x15'
62"	7	24	5	9.5'x15'

The vertical model is sturdy in construction, simple to operate and easy to handle. The flute roller, mounted on roller bearings for smoother running and longer life, impart the proper impression on the board. The machine is provided with manual operated twin shaft reel stand. The heaters are provided for the appropriate conversion of paper to 2-ply. The variable speed motor shown is not standard with the machine but is recommended, at an additional cost.

Size Inches	in Motor (H.P.)	Heating Load (KW)	Floor Space(Ft)	Max Output(Rft/min)
32	3.0	13.5	6x12	75
42	3.0	18.0	7x12	75
45	5.0	18.0	7.5x12	75
52	5.0	21.0	8x13	75
62	7.5	24.0	9x14	75