



Standard Features

PRACHITIRTH TM Hydro Extractor Direct Drive

PRACHITIRTH Hydro Extractor machine Direct Drive Motor Self-Balancing This Machine has excellent performance with low noise and is vibration free due to its high speed rotation with automatic electromagnetic DC injection brake System Having Capacity of 15 to 50 kg. per charge with auto timed. Top loading, vibration less, inner basket and outer drum stainless steel with specially designed foundation frame for grouting facility of dismantling the inner basket without dismantling the outer body, complete with specially designed electric motor and control panel operates on 415 V, 3 Phase, 50 Hz AC supply.

Model	Capacity kegs	Cylinder Size	Drive Motor	Cylinder Speed	Drain	Overall Damnation WxDxH	Weight
PMC15DD	15 kg	500x300 20"x12"	2 HP	960 RPM	50mm	760x1000x1100	150 kg
PMC25DD	25 kg	600x350 24"x14"	3 HP	960 RPM	50mm	1000x1200x1100	250 kg
PMC35DD	35 kg	700x350 28"x14"	5 HP	960 RPM	75mm	1200x1200x1200	310 kg
PMC50DD	50 kg	900x400 36"x16"	7.5 HP	960 RPM	100mm	1450x1400x1250	600 kg



PRACHITIRTH Hydro Extractor Three Suspensions

PRACHITIRTH Hydro Extractor machine inner outer drum body is made from stainless steel. specially designed three leg spring mounted suspensions. High speed heavy duty garment NTN bearing housing. 100% spare replacement. each & every part of the model can be replaced instant because they are standard. all models are available in 3 phase or 1 phase as per order. We can also make new design machine as per your order & requirement unique design gives maximum out put. Variable speed drive for different type of fabrics are also possible.

Model	Capacity kegs	Cylinder Size	Drive Motor	Cylinder Speed	Drain	Weight
PMC20ss	20 kg	450x350 18"x14"	2 HP	960 RPM	50mm	250 kg
PMC30ss	30 kg	600x350 24"x14"	3 HP	960 RPM	50mm	400 kg
PMC40ss	40 kg	750x400 30"x16"	3 HP	960 RPM	75mm	550 kg
PMC50ss	50 kg	900x400 36"x16"	5 HP	900 RPM	100mm	900 kg
PMC100ss	100 kg	1050x400 42"x16"	7.5 HP	750 RPM	100mm	1300 kg



