Tumble Dryer









Front Loading, Open Pocket, Heavy Duty:

PRACHITIRTH Tumble Dryer

- The tumble drier use the heat exchange high quality to dry garments and other articles that have just been washed.
- The Complete stainless steel (AISI Grade 304) basket that holds the articles is precision punched in a CNC machine and is supported by self aligning
 ball bearing for a noiseless operation. The size of the perorations in the inner basket are optimally designed so as to ensure the right amount of air
 flow. The inner basket has stainless steel paddles manufactured on a CNC machine to ensure consistency in the lifting of garments.
- The outer body is completely powder coated in our in house powder coating facility to ensure a long life.
- An individual micro control based control system comes standard with this machine. Settings than are displayed and can be programmed include cycle times.
- Digital temperatures controls and Two Way Swatch. Individual micro control auto timed, auto-reverse & forward time.
- The heat exchange can be powered with steam, & electrical heated.
- A reversing inner basket to prevent garments from tangling and a large door opening for ease of loading and unloading articles come standard.
- Emergency stop button and a safety limit switch is pre installed to ensure safety of the operator.
- The lint filter is extremely large and very easy to clean (low the inner basket is doubly insulated with the finest quality mineral wool held in place by aluminum sheets on loaded spring hooked ties.

www.laundryequipment.in

Tumble Dryer









Model	Capacity (kgs)	Basket Size mm Inch	Drive Motor HP	Blower Motor HP	Steam Connection & Consumption	Air outlet (mm)	Electric Heating (kw)	Main Door Opening	Dimensions (W x D x H)	Net Weight (kgs)
PMC15DT	15	760x600 30"x24"	0.5	0.5	15mm BSP 20kg H/R	250x250	9 to 12	450mm	650x1150x1700	375
PMC30DT	30	914x914 36"x36"	1	1	15mm BSP 35kg H/R	300x300	16 to 20	600mm	1100x1350x1800	450
PMC60DT	60	1200x990 46"x39"	2	1.5	25mm BSP 50kg H/R	350x350	24 to 30	775mm	1350x1825x2300	670
PMC100DT	100	1650x1100 66"x44"	3	1.5 + 1.5	25mm BSP 90kg H/R	400x400	N/A	850mm	1900x2210x2700	900
PMC120DT	120	1800x1250 72"x50"	3	2 + 2	38mm BSP 120kg H/R	400x400	N/A	1050mm	2200x2600x3100	1100

ISO 9001-2008 certificate and Certified by CE, JANZ - BSCIC, NSIC

The Company reserves all the right to alter specifications and design without prior notice for further improvements.