

Agriculture Sector

Vertical Open well Submersible pumps



Specification

- 3.0 hp to 70.0 hp.
- Total head up to 500 metres.
- Discharge up to 10,000 LPM.

Salient Features:-

- High Grade Cast iron body
- Copper rotor
- Frictionless Bearings
- Can withstand high volt fluctuations
- High efficiency
- Trouble free performance

Horizontal Open well submersible pumps



Specification

- 3.0 hp to 10.0 hp.
- Total head up to 50 metres.
- Discharge up to 1000 LPM.

Salient Features:-

- High Grade Cast iron body
- Copper rotor
- Frictionless Bearings
- Can withstand high volt fluctuations
- High efficiency
- Trouble free performance

Submersible pumps
(For 4 inch Borewell)



Submersible pumps For 4'inch Bore well
0.5 hp to 3 hp Single Phase and
1 hp to 7.5 hp Three Phase

Submersible pumps
(For 6 inch Borewell)



Submersible pumps For 6'inch Bore well
2.0 hp to 30 hp Three Phase

Specification

Our product ranges from 0.5 H.P to 30 H.P. suitable for 4", 6" bore hole having a total head upto 500 metres and with a discharge upto 1400 LPM. For 8" bore holes and above we have motors upto 70 H.P. with a total head upto 500 metres and discharge upto 3300 LPM.

Salient Features:-

- Stainless steel body
- Copper rotor
- Frictionless Bearings
- Can withstand high volt fluctuations
- High efficiency
- Trouble free performance