

Slurry Pumps

"HITEC" Slurry Pumps are rugged, compact, efficient pumps to handle slurry successfully. These pumps can be useful in coal handling Plants, Power Plants, Steel Plants etc...

- Low Speed pumps hence minimum wear & tear
- High starting torque.
- Agitator at bottom. (Optional)
- Double tandem Mechanical Seals.
- "H" Class Insulation.



PERFORMANCE TABLE								
MODEL	0	4	8	12	16	20	24	28
	DISCHARGE IN LPM							
HSR 5	1400	1150	850	-	-	-	-	-
HSR 10	2200	1960	1480	860	300	-	-	-
HSR 15	3400	2900	2400	1150	750	-	-	-
HSR 25	4200	3400	2700	2100	1300	600	-	-

TECHNICAL SPECIFICATION							
MODEL	HP/kw	VOL.	PH	Hz	CABLE	OUTLET	WEIGHT IN KG
HSR 5	5/ 3.7	415	3	50	4 X 2.5 =10Mtr	100 mm	125
HSR 10	10/ 7.5	415	3	50	4 X 4.0 =10Mtr	100 mm	160
HSR 15	15/ 11.0	415	3	50	4 X 4.0 = 10Mtr	150 mm	215
HSR 25	25/ 18.6	415	3	50	4 X 4.0 = 10mtr	150 mm	280