

# Screw Drivers



**SM-802 1/4" AIR SCREWDRIVER(Pistol)**  
- Adjustable Clutch



**SM-842 AIR SCREWDRIVER**  
Straight - Adjustable Clutch



**SP - 310**  
SIDE EXHAUST  
Impact Screwdriver  
Twin Hammer



**SP - 310L**  
SIDE EXHAUST  
Impact Screwdriver  
Twin Hammer



**ANGLE TYPE TORQUE CONTROLLED**  
Shut-off Screw Driver



**STRAIGHT TORQUE CONTROLLED**  
Push / Lever start shut-off  
Screw Driver



**PISTOL  
TORQUE CONTROLLED**  
Shut-off Air Screw Drivers

## Pneumatic Screw Drivers

Model	Free Speed (RPM)	Capacity	Torque(Nm)	Air Inlet (N.P.T)	Hose Size (I.D)	Air Pressure (PSI)	Air Consu. (CFM)	Length(mm)	Weight(Kg)
SM-842	1,800	6mm	5-8	1/4"	3/8"	90	4	254	1.13
SM-802	1,800	6mm	5-8	1/4"	3/8"	90	4	177.8	1.13
SM-803	800	6mm	5-8	1/4"	3/8"	90	4	216	1.21
SP-310	8,000	8mm	15	1/4"	3/8"	90	7	198	1.1
SP-310L	7,700	8mm	15	1/4"	3/8"	90	7	193	1.27

## Auto Shut off Screw Drivers

T40PB	1000	6mm	0.5 - 3	1/4"	1/4"	90	4	180	0.43
T50PB	1400	6mm	0.7-5.5	1/4"	3/8"	90	4	215	0.77
T55PB	1000	6mm	0.7 - 6.5	1/4"	3/8"	90	4	215	0.77
T60PB	550	7mm	1.5-9.5	1/4"	3/8"	90	4	215	0.77
T65PB	300	8mm	3-18	1/4"	3/8"	90	4	215	0.81