

Balanced Belts

The offered metal conveyor belt for glass annealing lehr is used for the manufacture of packaging, decorative, ovenware and possible other types of glasses.



Sr. No.	Specifications	No. of Spirals Per Feet	No. of Cross Rods Per Feet	Spiral Wire Dia	Cross Wire Dia
1.	B-12-12-10-08	12	12	10 swg	08 swg
2.	B-12-12-3X2-10	12	12	Flat Wire of 3X2 mm.	10 swg
3.	B-18-12-3x2-10	18	12	Flat Wire of 3X2 mm.	10 swg
4.	B-24-19-10-09	24	19	10 swg	09 swg
5.	B-24-19-10-10	24	19	10 swg	10 swg
6.	B-24-19-12-10	24	19	12 swg	10 swg
7.	B-24-18-14-12	24	18	14 swg	12 swg
8.	B-30-15-10-10	30	15	10 swg	10 swg
9.	B-36-18-	36	18	Flat Wire of	10 swg

	3.5X1.5-10			3.5X1.5 mm.	
10.	B-36-20-3X2-10	36	20	Flat Wire of 3X2 mm.	10 swg
11.	B-36-22-12-10	36	22	12 swg	10 swg
12.	B-36-20-12-10	36	20	12 swg	10 swg
13.	B-36-18-10-10	36	18	10 swg	10 swg
14.	B-36-15-10-10	36	15	10 swg	10 swg
15.	B-36-24-16-14	36	24	16 swg	14 swg
16.	B-36-18-14-12	36	18	14 swg	12 swg
17.	B-60-40-2X1.5-14	60	40	Flat Wire of 2X1.5 mm.	14 swg
18.	B-60-40-16-14	60	40	16 swg	14 swg
19.	B-60-24-16-14	60	24	16 swg	14 swg
20.	B-60-28-18-16	60	28	18 swg	16 swg
21.	B-72-24-14-12	72	24	14 swg	12 swg
22.	B-72-24-16-14	72	24	16 swg	14 swg