Brass Fittings



Microtech offer

- Brass Compression Fittings
- Brass Flare Fittings
- Brass Hose Fittings
- Brass Air Brake Fittings
- Brass Pipe Fittings
- Brass Garden Fittings
- Brass Push Fittings
- Brass Valve Fittings
- Sanitary Fittings

Threads:

- ISO metric (MM Threads)
- Inches Threads
- UNEF Threads
- NPTF Threads
- NPT Threads
- BSP Threads
- BSPT Threads
- UNC & UNF Threads
- Any Special Threads as per customers requirements

Material:

- Free Cutting Brass IS 319 Type (I) or
- Free Cutting Brass As Per BS 249 Type (I) or
- Any Special Brass Material Composition As Per Customers Requirement

Platting: Natural Brass, Chrome & Nickel Plated, or Any Coating As Per Customer Specification

Use With:

Copper Tube

Brass Tube

Aluminium Tube

Pressure: Working pressure up to 2000 psi with a 4:1 safety factor depending on tube size.

Temperature Range: 65° F to 250° F with metal tube.

Brass UPVC, CPVC, PPR linserts & Fittings:

Available: Plain, Hexagonal, Cross Knurling & Straight Knurling Etc.

Sizes: 1/2", 3/4", 1", 1.1/4", 1.1/2", 2"

Threads: BSP & BSPT (Parallel & Taper Threads)

Designed & developed as per customer's requirement.

Material:

- Free Cutting Brass IS 319 Type (I) or
- Free Cutting Brass As Per BS 249 Type (I) or
- Any Special Brass Material Composition As Per Customers Requirement

Platting: Natural Brass, Chrome & Nickel Plated, or Any Coating As Per Customer Specification