

## Enamelled Round Aluminium Wire



Enamelled aluminium wire is produced as per IEC, IS, BS, NEMA standards. Our customers are based all over India and includes large & medium Electrical equipment manufacturers and retailers for replacement / repairing sector.

Particular	Thermal Class	Specification	Size Range
Polyester Enamelled round aluminium wire	130	IS 13730 / IEC 60317 Part - 9:2000	16 SWG to 27 SWG 1.6 mm to 0.4 mm
Modified Polyester Enamelled round aluminium wire	155	IS:13730 / IEC 60317	16 SWG to 27 SWG 1.6 mm to 0.4 mm
Polyesterimide Enamelled round aluminium wire	180	IS:13730 / IEC 60317 Part - 15:1996	16 SWG to 27 SWG 1.6 mm to 0.4 mm
Self Solderable (Polyurethane) Enamelled round aluminium wire	155	IS:13730 / IEC 60317	16 SWG to 27 SWG 1.6 mm to 0.4 mm
Dual Coated Polyesterimide (Base coat) With Polyamide -imide (Top coat) round aluminium wire	200	IS:13730 / IEC - 60317 Part : 25:1993	16 SWG to 27 SWG 1.6 mm to 0.4 mm

### Packing

PT-15, PT-25, PT45, PT-90 & as per customers requirement.

### Application

Electrical Motors / Transformers / Automobile / Home Appliances / Light Fittings / Fans / Pump & Other Electrical & Electronic Equipments.