Temperature Gauge



Bimetal Gauge

Manufacturer & Exporter of Bi Metal Temperature Gauge & Mercury In Steel And Vapour. Our product range also comprises of Pressure Gauge, Duplex Pressure Gauges and Industrial Equipments.

We offer our client an excellent quality range of Bi-Metallic Temperature Gauges, which are manufactured from high grade quality raw materials. These Bi-Metallic Temperature Gauges can be customized as per our precious customers specifications. These Bi-Metallic Temperature Gauges are widely known for its durability and quality. Our major markets are USA and European Countries.

Other Information

Pay Mode Terms: T/T (Bank Transfer)

Minimum Order Quantity: 5000 Pieces

Port of Dispatch: KOLKATA

Production Capacity: 5000 pcs month

• **Delivery Time**: 6 weeks

Packaging Details: As per the specification of the consumer and design.



Mercury In Steel And Vapour

Types	Rigid Stem & Distance (capillary)
Dial Size	100, 150 & 200 mm.
Accuracy	1% of range span.
Ambient Compensation	with Bi-metal
Bulb Stem & Connection	Mild Steel or Stainless Steel
Case & Bezel	Cast Alluminiom Stove enabelled black weatherproof case with inner
	screwed type ABS Plastic, bezel.
Bulb Dia	16 mm (Standard) 12 mm.
Stem Dia	9 mm.
Immersion Length	Adjustable upto 300 mm.
Capillary	Copper, PVC on Copper, Stainless Steel, 3 meters Standard (maximum 15 meters)
Connection	3/4" BSP (M), other on request.
Mounting	1. Vertical (bottom entry) & Horizontal (back entry) with adjustable union
	for Rigid stem type.
	2. Panel (surface) with bottom entry & flush panel back entry with
	adjustable union for distance (capillary).
Range	-40 to 40, -20 to 500C, -38 to 50, 50, 100, 120, 150, 200, 250, 300, 400,
	500 & 6000C
Accessories	Antivibration Spring, Single & Double Electric Contact & Thermowell.