Level Indicators

Price And Quantity

- Price Range 11700.00 54900.00 INR
- Price 12600 INR
- Minimum Order Quantity 1 Piece
 Trade Information
- Main Domestic Market All India Product Description



Being an ISO 9001:2008 certified organization, Kabir Instruments & Technology is manufacturing, exporting and supplying a fine gamut of Level Indicators. These indicators are commonly used in automotive industries to install in vehicles and machines for indicating the level of fuel. The provided indicators are manufactured using quality assured raw materials and pioneering techniques by our deft professionals. Furthermore, client can avail these Level Indicators at market leading prices.

Features:

- Precisely engineered
- Application specific design
- High strength
- Easy to install
- Clear visibility
- Powder coated screen printed scale board
- Less corrosion powder coated finish
- Easy movement nylon roller pointer glides effortlessly
- No guide wire specially designed self centering float/anchor plate optional
- Non- stretching multi strand wire rope in ss/pp
- Dust free housing for pulleys minimizing friction in movement
- Easy to install, modular design
- Vapor tight-version for evaporating fluids

Applications:

Water, veg oil, molasses, caustics, brine, H2SO4 etc. Vapor sealed for solvent, HCL, and NH4OH etc

SPECIFICATIONS:

- Type : Reflex / Transparent
- Visibility: Full Visibility / Partial Visibility
- Liquid Chamber: Carbon Steel, S.S.304, S.S.304 (L), S.S.316, S.S.316 (L), P.P.
- Cover Plate: Carbon Steel, S.S.304, S.S.304 (L), S.S.316, S.S.316 (L), P.P.
- Gasket: CAF, PTFE, Graphoil, Non Asbestose Other On request
- Glass: Borosilicate Toughened of Indigenous Temperature Range upto 150oC, Klinger / Illamdur Make Imported Temperature Range Upto 400oC,

Other on request.

- Designed for high pressure & temperature liquid storage tanks in petrochemicals, fertilizers,
 Pharmaceuticals & Chemical industries.
- In reflex level gauges, the glass has precision groves cut inner side and mainly used for colorless liquids.
- In transparent level gauge, the glasses are without groves and arranged at the front and rear of a slotted liquid chamber and mainly used for colored liquids.
- Max. 3000 mm length in single piece.
- Imported/indigenous glasses on request.
- Frost free arrangement on request.