Analytical Balance



Features:

- Fast stabilazation in 2 secs.
- Ocompact foot print 198 mm x 294 mm.
- Rotary sliding doors for breeze break no extra space required at the rear for accessing weighing chamber.
- Removeable breeze brake for fast and simple cleaning.
- ① Clear, Reverse backlit LCD display provides excellent readability, even in a dimly- lit area.
- Tront mounted spirit level for easily adjusting the levelling feet.
- Twelve weighing units.
- **⊙** GLP/GMP/GCP/ISO Compliant Output.
- Adjustable Response Characteristics and Hold Function.
- Statistical Calculation Function.

Application:

- High precision weighing.
- Tor statistical weighing.
- To For animal weighing application.
- Occupant Comparator Sunction.
- Application which require weighing in dust and waterproof environment.
- O Underhook application.

Specification:

Model	HR250-A	HR250-AZ
Weighing capacity :	252 g	
Minimum weighing value:	0.1 mg	
Repeatability (standard deviation):	0 to 200 g: 0.1mg	
	200 to 252 g: 0.2 mg	
Linearity:	±0.3 mg	
Stabilization time:	Approx. 2 seconds	
Operating environment:	5 to 40 °C (41 to 104 °F), 85% RH or less (no condensation)	
Counting Mode:		
Minimum unit weight:	0.1mg	
No of samples:	10, 25, 50 or 100 pieces	
Interface:	RS232C	
Weighing pan size:	Ø90 mm	
Power supply:	AC adapter	
Internal Calibration	No	Yes
Clock & Calender function	No	Yes