

Spring Balancer



Technical Specifications

Model No	Capacity (kgs)	Cable travel (mtrs.)	Diameter of Cable (@ mm)	Mass (kgs)
HSB-2	0.5 - 2.0	1.0	3.0	1.0
HSB-3	1.0 - 3.0	1.3	3.0	1.4
HSB-5	2.5 - 5.0	1.3	3.0	1.5
HSB-7	4 - 7.0	1.3	3.0	1.6
HSB-9	4.5 - 9.0	1.3	4.0	3.4
HSB - 15	9.0 - 15.0	1.3	4.0	3.8
HSB - 22	15.0 - 22.0	1.5	5.0	8.0
HSB - 30	22.0 - 30.0	1.5	5.0	8.0
HSB - 45	30.0 - 45.0	1.5	5.0	11.0
HSB - 60	45.0 - 60.0	1.5	5.0	12.0
HSB - 75	60.0 - 75.0	1.5	5.0	12.0
HSB - 90	70.0 - 90.0	1.5	8.0	23.0
HSB - 110	90.0 - 110.0	1.5	8.0	26.0
HSB - 140	110.0 - 140.0	1.5	8.0	27.0
HSB - 170	140.0 - 170.0	1.5	8.0	29.0
HSB - 200	170.0 - 200.0	1.5	8.0	30.0
HSB - 220	200.0 - 220.0	1.5	8.0	33.0