

Bharath Jaw Crusher



BHARATH Jaw crushers are used as primary crushers, or the first step in the process of reducing rock. They crush primarily by using compression. The rock is dropped between two rigid pieces of metal, one of which then moves inwards towards the rock, and the rock is crushed because it has a lower breaking point than the opposing metal piece. We have supplied equipment for the construction, quarry, mining, and processing industries for over 56 years, and exporting equipment for 21 years.

Model	Feed Opening (mm)	Max Feed Size (mm)	Adjustable Range of Discharge Opening (mm)	Capacity (t/h)	Electric power (kw)	Weight (t)	Overall size LxWxH (mm)
BIW-150x250	150x250	125	10-40	1-5	5.5	0.81	875x758x850
BIW-250x400	250x400	210	20-60	5-20	15	2.8	1450x1315x1296
BIW-400x600	400x600	340	40-100	25-65	30	6.5	1565x1732x1586
BIW-500x750	500x750	425	50-100	45-80	55	10.1	1892x2054x1853
BIW-600x900	600x900	500	65-160	70-150	55-75	15.5	2520x1840x2303
BIW-750x1060	750x1060	630	80-140	130-260	110	28	2320x2302x3110
BIW-900x1200	900x1200	750	95-165	220-500	110-132	50	3789x2826x3025